



FWX7850

cod. FWX-7850



MUSCOLI COINVOLTI MUSCLE GROUPS

- Femorali - Femorals
- Glutei - Gluteus
- Adduttori - Adductors
- Abduttori - Abductors



SISTEMA DI SPINTA a leveraggio singolo
 REGOLAZIONI: altezza dei rulli di spinta su 5 livelli, profondità su 4 livelli
 DIMENSIONI PRODOTTO: 1170x1240x1525 mm
 PESO MAX UTILIZZATORE 180 Kg
 PESO MAX CARICABILE 150 Kg
 PESO: 89 kg
 CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-2 classe S)

SINGLE PUSH leverage system
 ADJUSTMENTS: push rollers height on 5-level, width on 4-level
 SET UP SIZE: 1170x1240x1525 mm
 MAX USER WEIGHT 180 Kg
 MAX LOADABLE WEIGHT 150 Kg
 WEIGHT: 89 kg
 COMMERCIAL USE (EN20957-1 / EN957-2 class S)

- Struttura tubolare in acciaio a sezione quadrata 50x50 mm - spessore 3 mm e rettangolare 50x80 mm spessore 3 mm.
- Verniciatura doppia a polveri epossidiche, antigraffio. Trattamento dei tubolari con sabbiatura e fosfatazione
- Sistema di cuscinetti POWER GRADE per garantire uno scorrimento preciso e progressivo
- Cuscini in schiuma ad alta densità con rivestimento in PU

- Structure squared heavy-duty steel tubing 50x50 mm - thickness 3 mm and rectangular heavy-duty steel tubing 50x80 mm - thickness 3 mm
- Double heavy duty powder coating painting, scratch-resistant. Tubing treatment with sandblasting and phosphating process
- Pulleys system POWER GRADE bearings for a smooth and precise action
- High-density foam cushions with PU upholstery

